



W I R M A N

10KVA

SILENT



Model		WIRMAN 10KVA SILENT
<b>GENERATOR</b>	Frequency (HZ)	50
	AC output (KVA)	10
	Rated AC voltage (V)	220/380
	Power factor	1
	DC output (V)	12V/8.3A
	Phase	Three phase
	Alternator type	Self-excited, 2-pole alternator
	Starting system	Electric
	Noise level (Dba/7m)	68-72
	Fuel tank capacity (L)	16
	Continuous running time (hr)	7.8
<b>ENGINE</b>	Engine model	HR192FD
	Engine type	Single-cylinder, vertical, 4-stroke air-cooled diesel engine
	BorexStroke (mm)	92x75
	Fuel consumption rate (g/kw.h)	≤280
	Fuel	0# or -10# light diesel oil
	Lubrication oil volume (L)	1.65
	Combustion system	Direct Injection
<b>STANDARD FEATURES</b>	Voltmeter	YES
	AC output socket	2
	AC circuit breaker	YES
	Oil warning light	YES
	Oil alert	YES

<b>OPTIONAL FEATURES</b>	DC circuit breaker	OPTIONAL
	Calculagraph	OPTIONAL
	Big wheel	OPTIONAL
	Three phase voltage	OPTIONAL
	Current meter	OPTIONAL
	ATS	OPTIONAL
	Remote control	OPTIONAL
<b>DIMENSIONS</b>	Packing dimation (LxWxH) (cm)	93x56x74
	Gross weight (kgs)	172

1