



W I R M A N

10KVA



Model		WIRMAN 11KVA
GENERATOR	Frequency (HZ)	50
	AC output (KVA)	11
	Rated AC voltage (V)	220/380
	Power factor	1
	DC output (V)	12V/8.3A
	Phase	Three phase
	Alternator type	Self-excited, 2-pole alternator
	Starting system	Manual or electric
	Noise level (Dba/7m)	80-85
	Fuel tank capacity (L)	12.5
	Continuous running time (hr)	5.9
ENGINE	Engine model	HR192FD
	Engine type	Single-cylinder, vertical, 4-stroke air-cooled diesel engine
	BorexStroke (mm)	92x75
	Fuel consumption rate (g/kw.h)	≤280
	Fuel	0# or -10# light diesel oil
	Lubrication oil volume (L)	1.65
STANDARD FEATURES	Combustion system	Direct Injection
	Voltmeter	YES
	AC output socket	2
	AC circuit breaker	YES
	Oil warning light	YES
Oil alert	YES	

OPTIONAL FEATURES	DC circuit breaker	YES
	Calculagraph	YES
	Big wheel	YES
	Three phase voltage	YES
	Current meter	NO
	ATS	NO
	Remote control	NO
DIMENSIONS	Packing dimation (LxWxH) (cm)	71x50x64
	Gross weight (kgs)	120