



W I R M A N

8.5KVA



| Model | | WIRMAN 8.5KVA |
|-------------------|--------------------------------|--|
| GENERATOR | Frequency (HZ) | 50 |
| | AC output (KVA) | 8.5 |
| | Rated AC voltage (V) | 220/380 |
| | Power factor | 1 |
| | DC output (V) | 12V/8.3A |
| | Phase | Three phase |
| | Alternator type | Self-excited, 2-pole alternator |
| | Starting system | Electric |
| | Noise level (Dba/7m) | 68-72 |
| | Fuel tank capacity (L) | 16 |
| | Continuous running time (hr) | 8.5 |
| ENGINE | Engine model | HR186FA |
| | Engine type | Single-cylinder, vertical, 4-stroke air-cooled diesel engine |
| | BorexStroke (mm) | 86x72 |
| | Fuel consumption rate (g/kw.h) | ≤280 |
| | Fuel | 0# or -10# light diesel oil |
| | Lubrication oil volume (L) | 1.65 |
| | Combustion system | Direct Injection |
| STANDARD FEATURES | Voltmeter | YES |
| | AC output socket | 2 |
| | AC circuit breaker | YES |
| | Oil warning light | YES |
| | Oil alert | YES |

| | | |
|--------------------------|--------------------------------|----------|
| OPTIONAL FEATURES | DC circuit breaker | OPTIONAL |
| | Calculagraph | OPTIONAL |
| | Big wheel | OPTIONAL |
| | Three phase voltage | OPTIONAL |
| | Current meter | OPTIONAL |
| | ATS | OPTIONAL |
| | Remote control | OPTIONAL |
| DIMENSIONS | Packing dimention (LxWxH) (cm) | 93x56x74 |
| | Gross weight (kgs) | 163 |

