



WM10000

SILENT

SILENT CANOPY DIESEL · THREE PHASE

10 kVA

AC OUTPUT

230/380 V

RATED VOLTAGE

3 ~

THREE PHASE

60 dB(A)

NOISE AT 7 M

GENERATOR

Frequency	50 Hz
AC output	10 kVA
Rated AC voltage	230 / 380 V
Power factor	1
DC output	12 V / 8.3 A
Phase	Three phase
Alternator type	Self-excited, 2-pole
Starting system	Electric
Noise level (7 m)	60 dB(A)
Fuel tank capacity	16 L
Continuous running time	7.8 h

STANDARD FEATURES

Voltmeter	YES
AC output socket	2
AC circuit breaker	YES
Oil warning light	YES
Oil alert	YES

ENGINE

Engine model	HR192FD
Engine type	Single-cylinder, vertical, 4-stroke, air-cooled diesel
Bore × stroke	92 × 75 mm
Fuel consumption	≤ 280 g/kW·h
Fuel	0# or -10# light diesel
Lubrication oil volume	1.65 L
Combustion system	Direct injection

OPTIONAL FEATURES

DC circuit breaker	YES
Calculagraph	OPTIONAL
Big wheel	YES
Three phase voltage	YES
Current meter	YES
ATS	OPTIONAL
Remote control	OPTIONAL

DIMENSIONS

Packing dimensions (L×W×H)	93 × 56 × 74 cm
Gross weight	172 kg