



WM11000E

OPEN FRAME DIESEL · THREE PHASE

11 kVA

AC OUTPUT

220/380 V

RATED VOLTAGE

3 ~

THREE PHASE

5.9 h

RUNNING TIME

GENERATOR

Frequency	50 Hz
AC output	11 kVA
Rated AC voltage	220 / 380 V
Power factor	1
DC output	12 V / 8.3 A
Phase	Three phase
Alternator type	Self-excited, 2-pole
Starting system	Manual or electric
Noise level (7 m)	80-85 dB(A)
Fuel tank capacity	12.5 L
Continuous running time	5.9 h

STANDARD FEATURES

Voltmeter	YES
AC output socket	2
AC circuit breaker	YES
Oil warning light	YES
Oil alert	YES

ENGINE

Engine model	HR192FD
Engine type	Single-cylinder, vertical, 4-stroke, air-cooled diesel
Bore × stroke	92 × 75 mm
Fuel consumption	≤ 280 g/kW·h
Fuel	0# or -10# light diesel
Lubrication oil volume	1.65 L
Combustion system	Direct injection

OPTIONAL FEATURES

DC circuit breaker	YES
Calculagraph	YES
Big wheel	YES
Three phase voltage	YES
Current meter	NO
ATS	NO
Remote control	NO

DIMENSIONS

Packing dimensions (L×W×H)	71 × 50 × 64 cm
Gross weight	120 kg