



WM13000

OPEN FRAME DIESEL · SINGLE PHASE

13 kVA

AC OUTPUT

220 V

RATED VOLTAGE

1 ~

SINGLE PHASE

9.5 h

RUNNING TIME

GENERATOR

Frequency	50 Hz
AC output	13 kVA
Rated AC voltage	220 V
Power factor	1
DC output	12 V / 8.3 A
Phase	Single phase
Alternator type	Self-excited, 2-pole
Starting system	Electric
Noise level (7 m)	80-85 dB(A)
Fuel tank capacity	23 L
Continuous running time	9.5 h

STANDARD FEATURES

Voltmeter	YES
AC output socket	2
AC circuit breaker	YES
Oil warning light	YES
Oil alert	YES

ENGINE

Engine model	HR198FA
Engine type	Single-cylinder, vertical, 4-stroke, air-cooled diesel
Bore × stroke	98 × 84 mm
Fuel consumption	≤ 230 g/kW·h
Fuel	0# or -10# light diesel
Lubrication oil volume	1.65 L
Combustion system	Direct injection

OPTIONAL FEATURES

DC circuit breaker	OPTIONAL
Calculagraph	OPTIONAL
Big wheel	OPTIONAL
Three phase voltage	OPTIONAL
Current meter	OPTIONAL
ATS	OPTIONAL
Remote control	OPTIONAL

DIMENSIONS

Packing dimensions (L×W×H)	95 × 63 × 72 cm
Gross weight	155 kg